

Carbon-Ti X-Hub ROAD SP Front



ITALIANO

DESTINAZIONE

X-Hub ROAD SP Front è un prodotto molto leggero e sofisticato ed è concepito per l'utilizzo nelle competizioni o ricreativo.

COMPATIBILITA'

X-Hub ROAD SP Front è compatibile con il classico bloccaggio ruota quick release standard e battuta asse da 100 mm.

CARATTERISTICHE TECNICHE

X-Hub MTB SP Front presenta raffinatezze meccaniche e un rapporto rigidità/peso ai massimi livelli, il corpo è lavorato dal pieno ed alleggerito minuziosamente tramite macchine CNC, la meccanica presenta un asse da 17 mm a sezione variabile su cui sono montati cuscinetti sigillati di altissima qualità con sistema di precarico esterno.





fig.A



DIMENSIONI

N° fori per raggi: 20
 Diametro interno flangia: Ø 30 mm
 Diametro asse: 17 mm
 Battuta asse: 100 mm
 Tipo bloccaggio: quick release
 Tensione dei raggi max: 90 Kg




fig.B

REGOLAZIONE BEARING PRELOAD SYSTEM (BPS)

Il registro esterno di precarico dei cuscinetti (cod. XHRFADLMN) è azionabile con due sole dita. Mai usare pinze od altri utensili.

Il mozzo viene consegnato perfettamente regolato dalla fabbrica dunque non modificare il precarico se non necessario.

La regolazione del precarico si rende eventualmente opportuna quando la ruota regolarmente installata nella forcella presenta un evidente gioco laterale o risulta molto frenata. In caso di gioco, dopo aver allentato il grano (parte n°6) ruotando in senso antiorario con una chiave esagonale da 1,5 mm, agire sulla ghiera di regolazione in senso orario (CLOSE). Nel caso in cui la ruota sia troppo frenata ruotare la ghiera in senso antiorario (LOOSEN). Ad operazioni concluse serrare nuovamente il grano. La regolazione è ottimale quando la ruota non presenta un gioco laterale evidente e scorre fluida fino all'arresto. Una regolazione scorretta del BPS invece, potrebbe compromettere la performance del mozzo fino a danneggiare i cuscinetti. Qualora la regolazione del BPS non fosse sufficiente a recuperare la piena efficienza del mozzo è consigliabile la sostituzione dei cuscinetti. Fare eseguire tale operazione esclusivamente a personale qualificato ed utilizzare ricambi originali Carbon-Ti.

SMONTAGGIO, PULIZIA E LUBRIFICAZIONE

Il mozzo può essere aperto facilmente inserendo nelle estremità dell'asse 2 chiavi esagonali da 5 mm, ruotando in senso antiorario fino al completo svitamento della chiusura asse (cod. XHRSLFCLMN). Successivamente sfilare l'asse (cod. XHRSLFAXMN) eventualmente picchiettando delicatamente con l'ausilio di un martello in gomma. Svitare completamente la ghiera del BPS, pulire i filetti e verificare le condizioni degli stessi. Pulire e verificare lo stato dei cuscinetti, sostituendoli qualora presentassero evidenti segni di usura. L'inserimento dei cuscinetti va eseguito esclusivamente mediante l'utilizzo di attrezzi per montaggio cuscinetti professionale (pressa).

RIMONTAGGIO

Riavvitare la ghiera BPS sino alla posizione di fine corsa, inserire l'asse nella sede dei cuscinetti dopo averlo lubrificato con grasso e picchiettando eventualmente con il martello di gomma. Serrare con chiave dinamometrica la chiusura (cod. XHRSLFCLMN) ad una coppia di 6 Nm. Accertarsi che il cuscinetto sinistro sia correttamente a battuta con la chiusura dell'asse (cod. XHRSLFCLMN) dopodichè avvitare manualmente il BPS in senso orario sino alla corretta registrazione (vedi REGOLAZIONE BEARING PRELOAD SYSTEM).

Tabella elenco parti			
NUMERO	QTA'	CODICE	DESCRIZIONE
1	1	XHRSLFBD20(col.)	Corpo mozzo ant. 20 fori
2	1	XHRSLFAXMN	Asse anteriore 17mm
3	2	61803-2RS1	Cuscinetto 17x26x5 61803-2RS1
4	1	XHRSLFCLMN	Chiusura asse anteriore
5	1	XHRFADLMN	BPS anteriore
6	1	HSS3x3	Grano M3x3 in inox




fig.C

GARANZIA

I prodotti Carbon-Ti sono garantiti contro difetti di materiale e costruzione per un periodo di 2 anni dalla data di acquisto del primo utilizzatore, certificata dallo scontrino fiscale del negozio. La garanzia decade nel caso in cui la manutenzione ordinaria o straordinaria consigliata non sia stata eseguita. In caso di vizio, Carbon-Ti si impegna ad effettuare la sostituzione o la riparazione, a sua discrezione dell'elemento riconosciuto difettoso. Per essere accettato, il difetto deve essere comunicato dal primo proprietario al proprio rivenditore e da quest'ultimo, dopo averlo verificato, alla Carbon-Ti. La garanzia non copre i danni risultanti da trasporto, giacenza, incidenti, negligenze, colpi o cadute, mancato rispetto delle informazioni del libretto istruzioni, montaggio errato o con prodotti non compatibili, cattiva manutenzione, usura normale, modifiche o alterazioni del prodotto. La Garanzia non copre le parti soggette a normale usura come i cuscinetti.

X-Hub ROAD SP Front è 100% made in Italy



Via per Ospitaletto, 147 25046 Cazzago S.Martino (Brescia) – ITALY
 Web site: <http://www.carbon-ti.com> Email: info@carbon-ti.com



Scansionare per accedere al video di manutenzione dei mozzi SP

Carbon-Ti X-Hub ROAD SP Front



ENGLISH

DESTINATION



X-Hub ROAD SP Front is a very light and sophisticated product and it is intended for competition or recreational use.

COMPATIBILITY

X-Hub ROAD SP Front is compatible with the classic standard quick release, with 100 mm width.


FEATURES

X-Hub ROAD SP Front presents refinements and a mechanical stiffness/weight ratio at the highest level, the Al7075-T6 body is machined from solid and is lightened by meticulous works with CNC machines. The Al7075-T6 17 mm diameter axle has a variable thickness, two high quality sealed bearings with external preload system provide reliability and smoothness.



SPECIFICATIONS

- Spoke hole drilling: 20
- Internal flange diameter: \varnothing 30 mm
- Axle diameter: 17 mm
- Axle width: 100 mm
- Frame attachment: quick release
- Maximum hub spoke tension: 90 Kg



BEARING PRELOAD SYSTEM TUNING (BPS)

The external Bearing Preload System (cod. XHRFADLMN) is operable with only two fingers. Never use pliers or other tools.

The hub comes perfectly tuned from the factory so do not modify the preload if not necessary.

The preload adjustment may be needed when the wheel properly installed in the fork has an evident side play or the rotation not is enough smooth. In case of play, after loosening the grub screw (part n°6) with a 1,5 mm hex key, turn the Bearing Preload System (BPS) in a clockwise direction (CLOSE). In case the rotation is not smooth enough turn counterclockwise direction (LOOSEN). Tighten the grub screw. The setting is optimal when the wheel does not have any evident side play and rolls very smoothly. Improper adjustment of the BPS however could adversely affect the performance of the hub and damage the bearings. If the adjustment of the BPS is not enough to recover the full efficiency of the hub it is advisable to replace the bearings. This work must be done only by skilled mechanics using original Carbon-Ti spare parts.


DISASSEMBLY, CLEANING AND LUBRICATION

The hub can be easily opened inserting two 5 mm hex keys in the axle sides, turn counterclockwise until complete loosening of the axle end (cod.XHRSLFCLMN). Then remove the axle (cod. XHRSLFAXMN) possibly gently hitting with a rubber mallet. Unscrew the BPS completely, clean the threads and check their condition. Clean and check the condition of bearings and replace them if they are damaged. The insertion of the bearings should be exclusively done with professional tools for bearings mounting (bearing cup press).

REASSEMBLY

Turn the BPS to the end position, insert the axle into the bearings housing after lubricating grease, maybe using a rubber mallet. Tighten the axle end (cod.XHRSLFCLMN) with a torque wrench to a 6 Nm torque. Be sure that the left bearing is accurately placed against the axle end (cod.XHRSLFCLMN) then turn the BPS clockwise until the proper adjustment (see BEARING PRELOAD SYSTEM TUNING).

Part List Tab			
NUMBER	QTY	CODE	DESCRIPTION
1	1	XHRSLFBD20(col.)	20 holes front body
2	1	XHRSLFAXMN	17mm front axle
3	2	61803-2RS1	61803-2RS1 bearing
4	1	XHRSLFCLMN	Front axle end
5	1	XHRFADLMN	Front BPS
6	1	HSS3x3	M3x3 Inox Grub Screw



WARRANTY

Carbon-Ti products are guaranteed against any defects for a period of 2 years from the date of purchase by the first owner, registered by the dealer. The warranty is void if the advised ordinary or extraordinary maintenance not been performed. In case of defects, Carbon-Ti is committed to replace or repair, at its discretion, the part recognised as defective. To be accepted, the rider compliant must be communicated to Carbon-Ti through the dealer/importer after his own control. If Carbon-Ti after sales checking reveals that the damage is due to one of the reasons mentioned in the following paragraph, the replacement is no longer accepted and the defective item is sent back to the plaintiff who supports the shipping fees. The warranty does not cover damage resulting from transportation, warehousing, accidents, negligence, impact or falls, non-compliance with the information in the instruction manuals, assembly errors, assembly using non-compatible products, bad maintenance, modifications or alterations to the product. The warranty does not cover parts subject to normal wear such as bearings.

X-Hub ROAD SP Front is 100% made in Italy



Via per Ospitaletto, 147 25046 Cazzago S.Martino (Brescia) – ITALY
Web site: <http://www.carbon-ti.com> Email: info@carbon-ti.com



Scan this QR code to watch the X-Hub SP maintenance video